

# FILT'RAY 1-month shower filter

Ref. AT030711

Sterile



## DESCRIPTION

**FILT'RAY 1-month shower filter**

**Ref. AT030711**

AQUATOOLS anti-Legionella and all-germ shower filter.  
 Device made from MBS.  
 Membrane type: tubular microfiltration.  
 Membrane made from polyethylene.  
 Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.  
 Filtration flow rate: 11.9 lpm at 3 bar and 4.5 lpm at 1 bar (filter only, excludes any flow rate restriction in the shower).  
 Maximum upstream pressure at the point-of-use: 5 bar.  
 Maximum lifespan: 1 month from installation.  
 Withstands thermal shocks: 70°C for 30 minutes.  
 Withstands chemical shocks: active chlorine levels up to 100 ppm for 1 hour (cumulative total).  
 Sterile filter.  
 FILT'RAY 2G sterile disposable water filters are:  
 CE marked Class I Medical Devices in Europe that comply with directive 93/42/CEE;  
 Class II Medical Devices in the U.S.A. with FDA-510(K) clearance;  
 Class I Medical Devices in Canada that comply with SOR/98-282.  
 Packaged in boxes of 10, each filter is individually wrapped and sterile.

## ADVANTAGES



Anti-Legionella and all-germ



Lifespan: 1 month from installation



Bubl'air Wash: longer filter life



Rapid installation with no tools required

## TECHNICAL CHARACTERISTICS

**FILT'RAY 1-month shower filter - Ref. AT030711**

Technology	Point-of-use filtration
Height	70mm
Length	225mm
Flow rate	11.9 lpm at 3 bar, 4.5 lpm at 1 bar
Lifespan	1 month
Norms	ACS CE JWRAS

