

FILT'RAY 2G 1-month tap filter

Ref. AT030718

Sterile



DESCRIPTION

FILT'RAY 2G 1-month tap filter

Ref. AT030718

AQUATOOLS anti-Legionella and all-germ tap filter, shower spray.
 Device made from MBS.
 Membrane type: tubular microfiltration.
 Membrane made from polyethylene.
 Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.
 Filtration flow rate: 6.3 lpm at 3 bar and 2.2 lpm at 1 bar (filter only, excludes any flow rate restriction in the tap).
 Maximum upstream pressure at the point-of-use: 5 bar.
 Maximum lifespan: 1 month from installation.
 Withstands thermal shocks: 70°C for 30 minutes.
 Withstands chemical shocks: active chlorine levels up to 100 ppm for 1 hour (cumulative total).
 Sterile filter.

FILT'RAY 2G sterile disposable water filters are:
 CE marked Class I Medical Devices in Europe that comply with directive 93/42/CEE;
 Class II Medical Devices in the U.S.A. with FDA-510(K) clearance;
 Class I Medical Devices in Canada that comply with SOR/98-282.
 Packaged in boxes of 10, each filter is individually wrapped and sterile.

TECHNICAL CHARACTERISTICS

FILT'RAY 2G 1-month tap filter - Ref. AT030718

Technology	Point-of-use filtration
Height	72mm
Length	75mm
Flow rate	6.3 lpm at 3 bar, 2.2 lpm at 1 bar
Lifespan	1 month
Norms	ACS CE JWRAS

ADVANTAGES



Anti-Legionella and all-germ



Lifespan: 1 month from installation



Bubl'air Wash: longer filter life



Rapid installation with no tools required

