

FILT'RAY 2G 2-month tap filter

Ref. AT030720

Sterile



DESCRIPTION

FILT'RAY 2G 2-month tap filter

Ref. AT030720

AQUATOOLS anti-Legionella and all-germ tap filter, shower spray.
 Device made from MBS.
 Membrane type: tubular microfiltration.
 Membrane made from polyethylene.
 Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.
 Filtration flow rate: 6.3 lpm at 3 bar and 2.2 lpm at 1 bar (filter only, excludes any flow rate restriction in the tap).
 Maximum upstream pressure at the point-of-use: 5 bar.
 Maximum lifespan: 2 months after installation.
 Withstands thermal shocks: 70°C for 30 minutes.
 Withstands chemical shocks: active chlorine levels up to 100 ppm for 2 hours (cumulative total).
 Sterile filter.
 FILT'RAY 2G sterile disposable water filters are:
 CE marked Class I Medical Devices in Europe that comply with directive 93/42/CEE;
 Class II Medical Devices in the U.S.A. with FDA-510(K) clearance;
 Class I Medical Devices in Canada that comply with SOR/98-282.
 Packaged in boxes of 10, each filter is individually wrapped and sterile.

ADVANTAGES



Anti-Legionella and all-germ



Lifespan: 2 months after installation



Bubl'air Wash: longer filter life



Rapid installation with no tools required

TECHNICAL CHARACTERISTICS

FILT'RAY 2G 2-month tap filter - Ref. AT030720

| | |
|------------|------------------------------------|
| Technology | Point-of-use filtration |
| Height | 72mm |
| Length | 75mm |
| Flow rate | 6.3 lpm at 3 bar, 2.2 lpm at 1 bar |
| Lifespan | 2 months |
| Norms | ACS CE WWRAS |

