

# FILT'RAY in-line filter, 4 months

Ref. AT030744

Non-sterile



## DESCRIPTION

**FILT'RAY in-line filter, 4 months**

**Ref. AT030744**

AQUATOOLS anti-Legionella and all-germ in-line filter.  
Suitable for filtering water to supply equipment used in the treatment of medical devices (e.g. endoscopes).  
Device made from MBS.  
Membrane type: tubular microfiltration.  
Membrane made from polyethylene.  
Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.  
Qualified water volume per duration of use: 6,000 litres.  
Filtration flow rate: 6.3 lpm at 3 bar and 2.2 lpm at 1 bar (filter only, excludes any flow rate restriction in the mixer/tap).  
Maximum upstream pressure at the point-of-use: 5 bar.  
Maximum lifespan: 4 months after installation.  
Resistance to thermal shocks: 70°C for 30 minutes.  
Resistance to chemical shocks: active chlorine levels up to 100 ppm for 4 hours (cumulative total).  
Non-sterile filter.  
Medical device CE Class I.  
Packaged in boxes of 10 pieces, each filter individually wrapped.

## TECHNICAL CHARACTERISTICS

**FILT'RAY in-line filter, 4 months - Ref. AT030744**

Technology	Point-of-use filtration
Flow rate	6.3 lpm at 3 bar and 2.2 lpm at 1 bar
Lifespan	4 months
Norms	ACS CE JWRAS

## ADVANTAGES



Anti-Legionella and all-germ



Lifespan: 4 months from installation



Bubl'air Wash: longer filter life



Rapid installation with no tools required

