

# FILT'RAY 2-month tap and wall shower filter

Ref. AT30250

Non-sterile



## DESCRIPTION

**FILT'RAY 2-month tap and wall shower filter**

**Ref. AT30250**

AQUATOOLS anti-Legionella and all-germ tap and wall-mounted shower filter, shower spray.

Device made from ABS.

Membrane type: tubular microfiltration.

Membrane made from polyethylene.

Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.

Qualified water volume per duration of use: 6,000 litres.

Filtration flow rate: 3 lpm at 1 bar, 5.5 lpm at 3 bar and 7.4 lpm at 5 bar (filter only, excludes any flow rate restriction in the tap).

Space saving, suitable for taps with a low spout height: H. 44mm, Ø 46mm.

Controlled management of retro-contamination: protective skirt and angled connector for optimal positioning (filter position can be adjusted so the water does not flow directly on to the waste).

Maximum upstream pressure at the point-of-use: 5 bar.

Maximum lifespan: 2 months after installation.

Resistance to thermal shocks: 70°C for 30 minutes.

Resistance to chemical shocks: active chlorine levels up to 100 ppm for 2 hours (cumulative total).

Non-sterile filter.

Reference for a single unit. Must be ordered in multiples of 10.

Packaged in boxes of 10 units.

## ADVANTAGES



Anti-Legionella and all-germ



Space saving



Optimised positioning: tilted connector



Lifespan: 2 months after installation

## TECHNICAL CHARACTERISTICS

**FILT'RAY 2-month tap and wall shower filter - Ref. AT30250**

| Technology | Point-of-use filtration                               |
|------------|---|
| Height     | 44mm  |
| Flow rate  | 3 lpm at 1 bar, 5.5 lpm at 3 bar and 7.4 lpm at 5 bar |
| Diameter   | 56mm  |
| Lifespan   | 2 months  |
| Norms      | ACS CE WRAS KTW BWGL                                  |

