# FILT'RAY 1-month shower head

Ref. AT20161

Sterile



# **DESCRIPTION**

FILT'RAY 1-month shower head

Ref. AT20161

AQUATOOLS anti-Legionella and all-germ shower filter.

Device made from ABS.

Membrane type: tubular microfiltration.

Membrane made from polyethylene.

Pore cut-off threshold: 0.1μm nominal and 0.2μm absolute sterilising grade.

Qualified water volume per duration of use: 3,000 litres.

Filtration flow rate: 6 lpm at 1 bar, 11.2 lpm at 3 bar and 13 lpm at 5 bar

(filter only, excludes any flow rate restriction in the shower valve).

Maximum upstream pressure at the point-of-use: 5 bar.

Maximum lifespan: 1 month after installation.

Resistance to thermal shocks: 70°C for 30 minutes.

Resistance to chemical shocks: active chlorine levels up to 100 ppm for 1 hour

(cumulative total).

Sterile filter.

Medical device CE Class Is.

Weight: empty filter 105g / full filter 186g.

Reference for a single unit. Must be ordered in multiples of 10.

Packaged in boxes of 10 units.

# **ADVANTAGES**



Anti-legionella and all-germ



Space saving



Lifespan: 1 month after installation



Quick to install without tools

### TECHNICAL CHARACTERISTICS

### FILT'RAY 1-month shower head - Ref. AT20161

Connector	M1/2"
Technology	Point-of-use filtration
Height	62mm
Length	194mm
Flow rate	6 lpm at 1 bar, 11.2 lpm at 3 bar and 13 lpm at 5 bar
Diameter	56mm
Lifespan	1 month
Norms	ACS WRAS BWGL

